

THRUST WASHERS											
DIMENSIONS						INTERCHANGE					
d		D		S		INA AS	SKF AS	FAG AS	IKO AS	Torrington FTRA	Torrington TRA
inch	mm	inch	mm	inch	mm						
0.250	6.350	0.687	17.450	.030-.032	.76-.81						TRA-411
0.312	7.925	0.750	19.050	.030-.032	.76-.81						TRA-512
0.375	9.525	0.812	20.625	.030-.032	.76-.81						TRA-613
0.394	10.000	0.945	24.000	0.0394	1	AS 1024	AS 1024	AS 1024	AS 1024	FTRA-1024	
0.472	12.000	1.024	26.000	0.0394	1	AS 1226	AS 1226	AS 1226	AS 1226	FTRA-1226	
0.500	12.700	0.937	23.800	.030-.032	.76-.81						TRA-815
0.562	14.275	1.000	25.400	.030-.032	.76-.81						TRA-916
0.591	15.000	1.102	28.000	0.0394	1	AS 1528	AS 1528	AS 1528	AS 1528	FTRA-1528	
0.625	15.875	1.125	28.575	.030-.032	.76-.81						TRA-1018
0.630	16.000	1.142	29.000	0.0394	1				AS 1629		
0.669	17.000	1.181	30.000	0.0394	1	AS 1730	AS 1730	AS 1730	AS 1730	FTRA-1730	
0.709	18.000	1.220	31.000	0.0394	1				AS 1831		
0.750	19.050	1.250	31.750	.030-.032	.76-.81						TRA-1220
0.787	20.000	1.378	35.000	0.0394	1	AS 2035	AS 2035	AS 2035	AS 2035	FTRA-2035	
0.875	22.225	1.437	36.500	.030-.032	.76-.81						TRA-1423
0.984	25.000	1.654	42.000	0.0394	1	AS 2542	AS 2542	AS 2542	AS 2542	FTRA-2542	
1.000	25.400	1.562	39.675	.030-.032	.76-.81						TRA-1625