



SAA15 BEARING

3/16" X 3/16" THIN SECTION BEARING

Type A
Angular Contact

SAA15 AGO

Circular pocket separator
3/32" balls

Type C
Radial Contact

SAA15 CLO

Snapover separator
3/32" balls

Type X
Four-Point Contact

SAA15 XLO

Snapover separator
3/32" balls

DIMENSION IN INCHES					CAPACITIES IN POUNDS										Appx Weight Pounds
Bore B	Outside Diam. D	Land Diam. L1	Land Diam. L2	C' Bore Diam. L3	TYPE A				TYPE C & X		TYPE X				
					Radial		Thrust		Radial		Thrust		Moment (Lbs-in)		
					Static	Dyn	Static	Dyn	Static	Dyn	Static	Dyn	Static	Dyn	
1.500	1.875	1.640	1.735	1.774	494	206	1,402	576	413	188	1,055	468	347	151	.039

1. For application load information contact Mechatronics engineering.

TYPE A INTERCHANGE	
KAYDON Part No.	Part No.
KAA15AGO	SAA15AGO

2. The maximum shaft or housing fillet radius that the bearing corners will clear for this series is .015.

TYPE C INTERCHANGE	
KAYDON Part No.	Part No.
KAA15CLO	SAA15CLO

3. Bearing width tolerance +.000-.005

TYPE X INTERCHANGE	
KAYDON Part No.	Part No.
KAA15XLO	SAA15XLO